

2900 Alumax Rd. Yankton, SD 57078 (605) 653-3247 sales@fairmfg.com

www.fairmfg.com

7200-LM Bale Processors



7200-LMH

7200-LM

Ultimate Speed & Versatility



Easily attaches to loaders & telehandlers

Saves thousands of dollars with greatly increased handling efficiency & processing times



Can carry 3 bales at a time

The side wall opposite the rotor can be lowered down to carry a third bale

Self-loading bale lift with spears & optional forks

Spear loading enables bales to be taken from the ground, stacks or pyramids without disturbing other bales.



High side walls & skirting

Contains loose hay, allowing for a clean operation when bedding from outside pens.



Can feed into bunks or windrows

Works great for spreading over gates & panels and into barns.

Can process 6x6 round & large square bales

Can spread straw up to 70 feet

Models for All Applications

7200-LM

 Fully self-contained requiring no electrical or hydraulics from the loader

- 173 hp diesel engine delivers exceptional performance for high capacity

Wireless controls: This allows for fast & easy hookup as well as the ability to operate the processor as a stand-alone unit.



7200-LMH

- Hydraulically driven from the wheel loader hydraulic system
- Requires min 35 gpm
- In-cab controls for all functions
- Simple design of few moving parts





Efficient Processing

Heavy Apron Table: Large shafts & double bearings for machine longevity

Few Moving Parts: Hay is ejected directly from the rotor eliminating locations to potentially plug

Patented Rotor: Parallel running bars create separation for easy twine removal



Specifications

7200-LM

Width 120"
Length 102"
Height 84"
Weight 7,000 Lbs.

Round Bale Capacity Square Bale Capacity

Loader Min. Static Tipping Load
Loader Min. Hydraulic Flow

NA

NA

Horsepower Bale Carrying Capacity 3

6x6 4x4x8

NÁ 173 HP

7200-LMH

Width | 98" | 102" | 102" | 84" | Weight | 4,500 Lbs.

Round Bale Capacity
Square Bale Capacity
4x4x8
Sin Static Tipping Load
45 000

Loader Min. Static Tipping Load 15,000 lbs
Loader Min. Hydraulic Flow 35 GPM

Horsepower Bale Carrying Capacity 3

t 4,500 Lbs. y 6x6 y 4x4x8 d 15,000 lbs

35 GPM NA

2900 Alumax Rd. Yankton, SD 57078 (605) 653-3247 sales@fairmfg.com

www.fairmfg.com